

## **Kint D130BS**

## **PVC Floor Marking Tape**

### **DESCRIPTION**

A thin premium grade plasticized PVC film coated with an aggressive rubber based adhesive with good characteristics. It is highly confirmable high-wearing feature and unaffected by most chemicals and moisture. It has been designed for all colour coding and floor lane marking applications.

### **APPLICATIONS**

- ◆ Primary construction industrial applications for floor marking of sport courts, factories, offices, banks, mails, parking lots.
- ◆ Decorating and protecting
- ◆ Colour coding
- ◆ Identifying industrial facilities(oil, water, and other products pipes)
- ◆ Used for marking clear and smoked glass application
- ◆ Hand application

### **TECHNICAL PROPERTIES**

<b>PROPERTY</b>	<b>VALUE</b>	<b>UNIT</b>	<b>TEST METHOD</b>
Total thickness	0.13	mm	ASTM-D-1000
Tensile Strength	20	N/cm	ASTM-D-1000
Elongation at break	180	%	ASTM-D-1000
to steel	1.5	N/cm	ASTM-D-1000
Unwind force	2-4	N/19mm	ASTM-D-1000

### **STANDARD PRESENTATION**

- ◆ Roll length : 22, 33, 55 metres
- ◆ Roll width : 48, 50mm
- ◆ Core : 76 mm cardboard core
- ◆ Packaging : As requirement
- ◆ Colours : Black/ Yellow, Red/White, Green/White  
Black, Red, Yellow, Green, Blue, White

### **RECOMMENDATIONS**

*Rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +10°C and +25°Cx65%R.H. Use within 12 months of receipt. The tape should be applied with sufficient tension to ensure an optimum bonding and a minimum of two layers with a half overlap. The final layer should be wrapped with a lower tension to prevent flagging effects. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.*